


PRODUCT DATA SHEET

Version: 06.10.2015 | 07:34 h

ITEM NO. 38909

Description	Frameseal bead with mesh
Specification	Self-adhesive PVC frameseal bead with protective lip and fibreglass mesh. Features a flexible movement element and a detachable adhesive tab to fix a protective sheet. Self-adhesive closed-cell foam tape. Profile width 9 mm, for thermal insulation, interior and exterior plaster. With perforated insertion leg for high-strength bonding. For visually and technically perfect soffit connections. Test-certified resistance to air, wind and heavy rain. Sd-value < 88 m, processing temperature +5° to +40°C. Generally frame seal beads may not be joined to produce a longer profile. Suitable for surfaces with a lightness value > 20.
Product Group	Plasterprofiles Soffit connecting profile
Product Category	Soffit connecting profile
Plaster Thickness	9 mm
Material	rigid PVC with soft PVC and glass fibre mesh
Colour	white
Length	150 cm 260 cm
Package	50 Piece



The present product sheet shows the current state of development of our products: with the publication of a new version this is no longer valid. Ensure that you always are using the most recent version of this information. Guarantees and liability upon delivery are defined in our general Terms of Business. Please follow the guidelines for use, fitting and siting. All information is subject to change.

Tender documents, fitting instructions and declarations of performance (where legally required) can all be found on our website. For the sake of the environment, please dispose of correctly!

PROTEKTORWERK
Florenz Maisch GmbH & Co. KG
Postfach 1420, D-76554 Gaggenau
Viktoriastr. 58, D-76571 Gaggenau

Tel.: +49 7225 977 - 0
Fax: +49 7225 9 77 - 111
info@protektor.com
www.protektor.com



PROFILE FÜR
MODERNES
BAUEN