

## PAVABASE *Solvent-free adhesive primer*



- Solvent-free
- Simple, reliable installation
- Primed area is easily visible
- Cleaning when still liquid with water

### Delivery form

	Contents per container [ml]	Box contents [units]	Accessories included
Tub	5000	–	–

### Field of application



### Technical data

Material	Aqueous bitumen emulsion, solvent-free
Minimum installation temperature for base and air [°C]	+5
Installation temperature Adhesive primer [°C]	+5 to +40
Temperature resistance [°C]	-40 to +80
Drying time at 20 °C, 50 % r.h., 300 g/m <sup>2</sup> [min.]	20
Drying time at 5 °C, 75 % r.h., 300 g/m <sup>2</sup> [min.]	50

### Usage on PAVATEX woodfibre boards, 300 g/m<sup>2</sup>

	Width [m]	g/m	ml/m	Yield 5l
PAVATAPE 150	0.15	45	45	~100 m
PAVATAPE 75	0.075	23	23	~200 m
PAVATAPE FLEX	0.08	24	24	~200 m
PAVATAPE 20	0.02	6	6	~800 m
PAVAFIX 60	0.06	18	18	~250 m

### Product description

PAVABASE is used as an adhesive medium for PAVATAPE and PAVAFIX 60 on PAVATEX woodfibre boards and other porous and mineral construction materials. PAVABASE is easy and reliable to install.

You will find details on usage and installation guidelines in the sealing brochure

### Storage

Cool (frost-free) and dry

### Shelf life

15 months unopened

### PAVATEX system guarantee

The high-performance adhesion and gluing components used in the PAVATEX system solutions ensure long-lasting, reliable system sealing in modern, multifunctional building envelopes - now also guaranteed by the new PAVATEX warranty. It offers comprehensive service if damage occurs, and therefore once again increases security for designers, installers and builders.

