



PAVABASE is used as a wash primer for PAVATAPE and PAVAFIX 60 on PAVATEX wood fibre boards and other porous or mineral materials. PAVABASE can be processed simply and easily.

Advantages:

- Solvent-free
- In 5 litre container
- Primed area clearly visible
- Cleaning in liquid state with water

Guidelines for professional installation:

The substrate must be dry, dust- and fat-free.

- ① Shake PAVABASE well before using. Apply the primer evenly and thoroughly to the substrate with a paint roller or brush.
- ② Before applying the PAVATAPE/PAVAFIX tape, let the primer air until it is no longer wet. The airing time may vary greatly and is dependent on the substrate, the temperature, the humidity of the air and the amount applied.

When fresh, PAVABASE can be cleaned with water. A hard wash primer can be removed mechanically or with pure benzene. Close the container tightly after use.

The airing time may be reduced using moderate heat supply, e.g. using a hair dryer.



Consumption with PAVATEX wood fibre boards, 300 g/m²

	Width [m]	ml/m	Reach 5l
PAVATAPE 150	0.15	45	~100 m
PAVATAPE 75	0.075	23	~200 m
PAVATAPE FLEX	0.08	24	~200 m
PAVATAPE 20	0.02	6	~800 m
PAVAFIX 60	0.06	18	~250 m

Delivery form

Bucket 5 l

Storage

Cool (frost-free) and dry

Lifespan

15 months, unopened

Technical specifications

Material Aqueous bitumen emulsion, solvent-free

Minimum processing temperature for substrate and air +5 °C

Processing temperature +5 to +40 °C

Temperature resistance -40 to +80 °C

Airing time +20° C, 50 % F, 300 g/m² 20 min.

Airing time +5° C, 75 % F, 300 g/m² 50 min.

1 PAVATEX Air and Wind-Tight Products and their applications at a glance...

10

	Butyl tapes			Acrylic tapes		Adhesives
	PAVATAPE 75/150	PAVATAPE FLEX	PAVATAPE 20	PAVAFIX 60	PAVAFIX SN BAND	PAVACOLL 310/600
Gluing onto PAVATEX wood fibre boards						
ISOLAIR L/ISOROOF-NATUR	👍*	👍*				👍
PAVATHERM-PLUS	👍*	👍*				👍
PAVATEX under-roof board bituminised	👍*	👍*				👍
PAVISO ¹⁾	👍*	👍*				
PAVAROOF-K ¹⁾	👍*	👍*				
PAVAROOF-W Plus ¹⁾	👍*	👍*				
PAVAPLAN 3F ¹⁾	👍*	👍*		👍		
Gluing onto PAVATEX membranes						
PAVATEX LDB 0.02		👍	👍	👍		👍
PAVATEX ADB	👍	👍	👍		👍	👍
PAVATEX DSB 2		👍	👍	👍		👍
PAVATEX DB 3.5		👍	👍	👍		👍
PAVATEX DB 28		👍	👍	👍		👍
PAVATEX RSP		👍	👍	👍		👍
At connections and penetrations/joint gaps adhering together on...						
Chipboards	👍*	👍*	👍*	👍		👍
Medium-density wood-fibre boards	👍*	👍*	👍*	👍		👍
OSB	👍*	👍*	👍*	👍		👍
Timber, planed	👍*	👍*	👍*	👍	👍	👍
Timber, raw	👍*	👍*	👍*	👍*	👍	👍
Cement-bonded chipboards	👍*	👍*	👍*	👍*		👍
Plasterboards	👍*	👍*	👍*	👍*		👍
Gypsum-fibre boards	👍*	👍*	👍*	👍*		👍
Concrete, smooth	👍*	👍*	👍*	👍*		👍
Plaster, mortar, gypsum	👍*	👍*	👍*	👍*		👍
Concrete, rough	👍*	👍*	👍*			👍
Bricks	👍*	👍*	👍*			👍
Metals, corrosion-protected	👍	👍	👍	👍		👍
Plastics (PE and PVC)	👍	👍	👍	👍		
Bitumen	👍	👍	👍			
(When in doubt, one needs to carry out one's own gluing attempts)				* substrate needs to be pretreated with PAVAPRIM or PAVABASE		
¹⁾ Only sold in CH						