



- Double-sided, high adhesive force, high initial adhesion
- Suitable for rough and smooth surfaces
- Fast and secure gluing of connections without drying time

Delivery form

	Box weight [kg]	Roll length [m]	Roll width [mm]	Box contents [units]
PAVATAPE 12	2.0	10	12	3

Field of application



Technical data

Material	Double-sided butyl rubber tape with thread inlay	
Thickness [mm]	3.5	
Minimum installation temperature for base and air [°C]	+5	
only with PAVAPRIM [°C]	-10	
Installation temperature Tape [°C]	+5 to + 30	
Temperature resistance [°C]	-40 to + 100	

Product description

Solvent-free and elastic airtight seal of butyl rubber. The durable seal is suitable for connecting all types of vapour barrier according to SIA 180 and DIN 4108-7. Also usable for water-tight bonding of roofing membranes.

You can find details on applications and installation guidelines in the technical or sealing brochure.

Storage

Cool and dry, protected from sunshine.

PAVATEX system guarantee

The high-performance adhesion and gluing components used in the PAVATEX system solutions ensure long-lasting, reliable system sealing in modern, multifunctional building envelopes - now also guaranteed by the new PAVATEX warranty. It offers comprehensive service if damage occurs, and therefore once again increases security for designers, installers and builders.

