

PAVATAPE 20 *Double-sided butyl rubber tape*



- Double-sided, high adhesive force
- No over-stretching through thread inlay
- Suitable for rough and smooth surfaces
- High resistance to ageing.

Delivery form

	Roll length [m]	Roll width [mm]	Box contents [units]
PAVATAPE 20	20	20	10

Field of application



Technical data

Material	Double-sided butyl rubber tape with thread inlay
Thickness [mm]	1.5
Minimum installation temperature for base and air [°C]	+5
only with PAVAPRIM [°C]	-10
Installation temperature Tape [°C]	+5 to + 40
Temperature resistance [°C]	-40 to + 80

Product description

For fast, long-lasting, airtight gluing of the overlaps and connections in PAVATEX membranes in indoor and outdoor applications. The butyl rubber tape exhibits a high adhesive force, and is impermeable to air and water. When gluing to porous or mineral contact surfaces, a preliminary coating of PAVABASE or PAVAPRIM is always applied.

You will find details on usage and installation guidelines in the sealing brochure

Storage

Cool and dry.

PAVATEX system guarantee

The high-performance adhesion and gluing components used in the PAVATEX system solutions ensure long-lasting, reliable system sealing in modern, multifunctional building envelopes - now also guaranteed by the new PAVATEX warranty. It offers comprehensive service if damage occurs, and therefore once again increases security for designers, installers and builders.

