

PAVATAPE FLEX *Stretchable butyl rubber tape*



- High resistance to ageing
- Highly flexible and supple
- Universally shapeable
- Can absorb the movement of the components

Delivery form

	Roll length [m]	Roll width [mm]	Box contents [units]
PAVATAPE FLEX	5	80	8

Field of application



Technical data

Material	Butyl rubber tape with stretchable foil carrier
Thickness [mm]	2
Minimum installation temperature for base and air [°C]	+5
only with PAVAPRIM [°C]	-10
Installation temperature Tape [°C]	+5 to +40
Temperature resistance [°C]	-40 to +90

Product description

Highly flexible butyl rubber tape, adhesive on one side, for long-lasting, easy sealing of PAVATEX boards and membranes, indoors and outdoors, at penetrations such as rafters, purlins, vent pipes etc. When gluing to woodfibre boards or other porous or mineral contact surfaces, a preliminary coating of PAVABASE or PAVAPRIM is always applied.

You will find details on usage and installation guidelines in the sealing brochure

Storage

Cool and dry.

PAVATEX system guarantee

The high-performance adhesion and gluing components used in the PAVATEX system solutions ensure long-lasting, reliable system sealing in modern, multifunctional building envelopes - now also guaranteed by the new PAVATEX warranty. It offers comprehensive service if damage occurs, and therefore once again increases security for designers, installers and builders.

